

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
24 June 2004 (24.06.2004)

PCT

(10) International Publication Number
WO 2004/052114 A1

(51) International Patent Classification⁷: A23D 7/00,
A23L 1/035, 1/19, B01F 17/00

(21) International Application Number:
PCT/EP2003/012503

(22) International Filing Date:
7 November 2003 (07.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02080177.5 10 December 2002 (10.12.2002) EP

(71) Applicant (for AL, AM, AT, AZ, BA, BE, BF, BG, BJ, BR, BY, CF, CG, CH, CI, CM, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, FR, GA, GE, GN, GQ, GR, GW, HR, HU, ID, IS, IT, JP, KG, KP, KR, KZ, LR, LT, LU, LV, MA, MC, MD, MG, MK, ML, MR, MX, MZ, NE, NI, NL, NO, PH, PL, PT, RO, RU, SE, SI, SK, SN, SY, TD, TG, TJ, TM, TN, TR, UA, UZ, VN, YU only): UNILEVER N.V. [NL/NL]; Weena 455, NL-3013 AL Rotterdam (NL).

(71) Applicant (for AE, AG, AU, BB, BZ, CA, CY, EG, GB, GD, GH, GM, IE, IL, KE, LC, LK, LS, MN, MW, NZ, OM, PG, SC, SD, SG, SL, SZ, TT, TZ, UG, VC, ZA, ZM, ZW only): UNILEVER PLC [GB/GB]; Unilever House, Blackfriars, London, Greater London EC4P 4BQ (GB).

(71) Applicant (for IN only): HINDUSTAN LEVER LIMITED [IN/IN]; Hindustan Lever House, 165/166 Backbay Reclamation, Maharashtra, 400 020 Mumbai (IN).

(72) Inventors; and

(75) Inventors/Applicants (for US only): LANSBERGEN, Gabriel, Jacobus [NL/NL]; Unilever R & D Vlaardingen, Olivier van Noortlaan 120, NL-3133 at Vlaardingen (NL). STAM, Theodorus [NL/NL]; Unilever R & D Vlaardingen, Olivier van Noortlaan 120, NL-3133 AT Vlaardingen (NL).

(74) Agent: SIKKEN, Antonius, H., J., M.; Unilever NV, Patent Department, Olivier van Noortlaan 120, NL-3133 AT Vlaardingen (NL).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: OIL IN WATER EMULSION

(57) Abstract: Non-dairy creams that comprise a mixture of triglyceride compositions, having a large variety in fatty acid and triglyceride compositions contained in the mix show improved storage stability and whipping performance. The complex mixtures of triglycerides are preferably obtained via interesterification.

WO 2004/052114 A1

Oil in water emulsion

Field of the invention

5

The invention relates to oil in water emulsions that are suitable for use as non-dairy creams.

Background to the invention

10

Water continuous emulsions containing from about 5 to 40 wt% fat are known in the art. Such emulsions are generally known as creams. The best known example of a cream is dairy cream. Dairy cream generally comprises about 40 wt% fat and is suitable for
15 use as a cooking cream, a whippable cream or a coffee cream.

Over the years, in order to improve the nutritional value and health aspects of creams, dairy fat has been (partly) replaced by vegetable fats. Creams wherein at least part of the dairy
20 fat has been replaced by a vegetable fat are referred to as non-dairy creams (NDC). Non-dairy creams are for example disclosed in EP-A-509579 which describes non-dairy creams based on liquid oils. The art has shown that the replacement of dairy fat with (generally more soft) vegetable fats may lead to a
25 deterioration of some product properties such as whip time, firmness after whipping, post hardening after whipping and storage stability of the product. These problems have been addressed in the art.

30 EP-A-682477 discloses low SAFA cream alternatives comprising a particular fat mixture which is a combination of fat A which is

high in SAFA (saturated fatty acid) and fat B which is high in PUFA (polyunsaturated fatty acid).

5 EP-A-691080 discloses the use of a food-acceptable salt derived from a multivalent metal or alkaline earth metal to improve the properties of a non-dairy cream.

JP 52078204 discloses compositions comprising 45% fat and
10 rather soft fats which result in fluffy creams after whipping.

Although the above described products may offer some product improvement, the known non-dairy creams are still not showing the desired combination of good whipping behaviour, limited
15 post hardening after whipping, limited or no thickening while packed, limited sensitivity to temperature cycling and storage and relatively low levels of saturated fatty acids.

It is an object of the invention to provide products that show
20 this desired combination of product properties.

Summary of the invention

We have surprisingly found that a mixture of triglyceride
25 compositions, having a large variety in fatty acid and triglyceride compositions contained in the mix, leads to non-dairy cream products fulfilling these objectives.

Therefore the invention relates to an oil in water emulsion
30 comprising emulsifier, and 5 to 40 wt% fat wherein the fat is characterised by a ratio of H₂U (triglycerides of 2 saturated fatty acids with chain length of at least 16 carbon atoms and

one cis-unsaturated fatty acid) in weight % on total fat divided by HM_2 (triglycerides of one saturated fatty acid with chain length of at least 16 carbon atoms and two saturated fatty acids with chain length of 10 to 14 carbon atoms) in weight % on total fat, plus H_2M (triglycerides of two saturated fatty acid with chain length of at least 16 carbon atoms and one saturated fatty acid with chain length of 10 to 14 carbon atoms) in weight % on total fat, is from 0.25 to 3.

10

Detailed description of the invention

In the context of the invention the terms "fat" and triglyceride are used interchangeably.

15

Triglycerides are molecules of glycerol esterified to 3 fatty acid residues. Triglycerides are characterised by their fatty acid composition and distribution over the 3 glycerol-ester positions.

20

The following abbreviations are used for fatty acids:

H means saturated fatty acid of 16 carbon atoms or longer (C_{16+} e.g. up to 24).

U means unsaturated fatty acid of any chain length, mono or polyunsaturated in cis-conformation.

25

E means unsaturated fatty acid in trans conformation. Trans level may be determined according to AOCS official method Ce 1f-96.

M means saturated fatty acid of 10-14 carbon atoms.

30 The fatty acid composition of triglycerides is given for example by:

H₂U: triglycerides of 2 saturated fatty acids with chain length at least 16 carbon atoms and one cis-unsaturated fatty acid.

M₃: triglycerides of three saturated fatty acids with chain length of 10 to 14 carbon atoms.

For the purpose of the invention, triglycerides comprising at least 20 wt%, preferably at least 30 wt% fatty acids with 12 carbon atoms (C12) on total fatty acid weight, are defined as 10 "laurics". Examples of laurics are coconut oil, palm kernel oil, babassu oil or derivatives thereof.

The fat compositions of the invention are characterised by the fatty acid composition of the triglycerides.

15

The invention relates to oil in water emulsions. These emulsions are preferably spoonable or pourable. Pourable means that the emulsion is a liquid (rather than a paste) and that it can be removed from its container by tilting the container, 20 whereby the emulsion flows out. Suitably, the emulsion will have a viscosity in the range of 0.1 to 40 dPa.s (deci-Pascal.s) when measured with a Haake viscosimeter type VT02, measured with head No.3, in measure beaker with 5 cm diameter at a temperature of 5 or 10 °C, measured after a few seconds 25 when value is about constant, rotation speed being 62.5 rotations per minute (rpm). The measurement is to be carried out 3 days after preparation of the emulsion and storage at 5 °C.

30 Preferably pourable creams have a viscosity of from 0.1 to 30 dPa.s, more preferred from 1 to 30 dPa.s, most preferred from 1 to 20 dPa.s.

Spoonable products are for example described in EP-A-691080.

The oil in water emulsion is also referred to as cream,
5 whippable cream or non-dairy cream. Preferably the creams are whippable.

The products according to the invention comprise a fat. The composition of the fat fulfils the requirement $H_2U/(HM_2 + H_2M)$ is
10 from 0.25 to 3, to ensure product stability and to reduce the thickening of the product on storage at constant temperature or at temperature cycling. Furthermore such fat contributes to the desired whippability and to ensure that products do not suffer from post hardening.

15

In the context of the invention, preferred products are whippable under conditions presented in the examples within 5 minutes, preferably within 4 minutes.

20 Post hardening is the increase of product hardness of a whipped product. This leads to products with a perceivable thickness/hardness, which is not desired. The method to determine post hardening is described in the examples. Preferably post hardening in terms of increase of Stevens value
25 at about 10 °C is less than 20%.

According to the invention the ratio $H_2U/(HM_2 + H_2M)$ is from 0.25 to 3, preferably 0.3 to 3.0, more preferably from 0.3 to 2, even more preferred from 0.35 to 1, most preferred from 0.5 to
30 0.80.

Products that show reduced ratio (below 0.25) of $H_2U/(HM_2 + H_2M)$ were found to show post hardening levels of more than 50%. Also these products often were thickening on storage, especially if

temperature cycling was applied. Temperature cycling is the storage of a product at 5 and 25 °C alternating whereby the product is at each temperature for at least 1 day.

5

According to a preferred embodiment the ratio of H_2U/M_3 is at least 0.3, preferably at least 0.5, more preferably at least 0.6, even more preferred at least 0.7, even most preferred at

10 least 0.9. Even more preferred the ratio of H_2U/M_3 is at most 10, preferably at most 5. Products that do not meet this requirement were found to show undesired levels of post hardening.

According to another embodiment, the ratio of H_2U/M_3 is from 0.5
15 to 10.

According to another preferred embodiment, the fats are chosen such that the level of H_2M plus HM_2 is at least 20 wt% on total weight of triglycerides, preferably from 20 to 25 wt% on total
20 weight of triglycerides.

According to another preferred embodiment, the amount of laurics is from 20 to 60 wt% on total fat. Higher levels than 60 wt% of laurics often lead to products with undesired product
25 properties. It is preferred that the amount of laurics is from 30 to 60 wt%, more preferred from 40 to 60-wt% on total fat.

Preferably the amount of H_2U is from 5 to 20, more preferably from 6 to 12 wt% on total fat.

30

The emulsion is suitable for all type of use such as cooking, topping, whipping. For many of its applications the product is consumed as such or after whipping. It is important that the

products have a good mouth feel and melting properties on eating them to make them suitable for these applications. The melting properties and mouth feel are largely determined by the solid fat content of the fat at consumption (in mouth) temperature. The higher the solids level around 37 °C, the more waxy the products taste and the longer it takes for them to create a pleasant melting sensation (which is e.g. achieved when chocolate is consumed). Therefore in a preferred embodiment the solid fat content of the fat at 35 °C is at most

10%, preferably at most 8%, more preferred at most 5%, even more preferred at most 4%. The method to determine the solid fat content of a fat (blend) at a certain temperature is described in the examples. The pretreatment of the fat has an impact on the solid fat content measured. Therefore these measurements are performed on fats that have been subjected to the following temperature regime:

- melt fat at 80 °C
- 5 minutes at 60 °C
- 60 minutes at 0 °C
- 30-35 minutes at each chosen measuring temperature

The solid fat content was found to influence the whipping and storage product properties as well. Suitable fats preferably have a solid fat content at 10 °C of at least 50%, preferably at least 55%, more preferred from 60 to 70%. Lower levels were found to increase the whip time.

The fat in the emulsions according to the invention is preferably derived from vegetable fat and/or fish oil. The presence of butter fat is tolerable but less preferred because of its price and because the products are preferably referred

to as non-dairy creams. Therefore preferred products contain less than 10 wt% butter fat on total fat. This level refers to added butter fat and does not include butter fat that may be
5 present in other ingredients such as butter milk powder.

Preferably the fat is selected from the group comprising palm oil, palm kernel oil, bean oil, rapeseed oil, coconut oil, sunflower oil and combinations thereof.

10

The fats may be derived from vegetable or fish oil without further treatment but optionally the oil is hydrogenated, interesterified or treated otherwise before use.

Partial hydrogenation is preferably avoided or carried out such
15 that the resulting level of trans-unsaturated fatty acids is kept to a minimum. Preferably in products according to the invention the level of trans-fatty acids (E) is less than 5 wt% of total fat, more preferred less than 3 wt% on total fat, most preferred essentially absent (less than 1 wt% trans fatty acid
20 on total fat).

Without wishing to be bound by any theory applicants believe that the benefits of the claimed fats are partly due to the fact that the claimed compositions are mixtures of
25 triglycerides comprising a broad variety of fatty acids and a broad variety of final triglyceride compositions. Such compositions are e.g. obtainable by interesterification of triglyceride mixtures. Therefore it is preferred that the fats at least partly consist of interesterified mixtures of
30 triglycerides, which are optionally combined with non-esterified fats.

Especially suitable are interesterified mixtures where the H-supplier is palm oil or palm oil stearine, which is esterified with laurics such as coconut oil. It will be appreciated
5 however that the requirements of the fat according to the invention may be fulfilled by a variety of triglyceride combinations which may be determined by a skilled person on the basis of his general knowledge provided he follows the guidance provided in this patent specification and examples.

10

To improve stability and whippability, the emulsions comprise an emulsifier. The emulsifier may be selected from any of the

suitable emulsifiers e.g. lecithin, monoglycerides,
15 diglycerides, citric acid (ester), lactic acid ester, polysorbate monostearate or combinations thereof.

The presence of unsaturated monoglycerides was found to positively influence whipping behaviour.

20 Therefore in a preferred embodiment the oil in water emulsion comprises monoglycerides in an amount of from 0.2 to 0.5 wt% on total emulsion weight.

The emulsions optionally comprise further ingredients that are
25 common for creams. Examples of such ingredients include, but are not limited to the following.

Proteins are often added to improve mouthfeel and taste of the products. Suitable proteins are for example derived from milk
30 or cream such as skim milk (powder), butter milk (powder). Suitable amounts of protein are from 0.5 to 5 wt%.

Thickeners are optionally added to improve the product stability. The thickener is preferably selected from the group comprising guar gum, carrageenan, xanthan gum, starch or a
5 combination thereof.

If added, the amount of thickener is preferably from 0.001 to 2 wt%, more preferred from 0.1 to 0.8 wt%.

Optionally the products comprise a sugar, e.g. glucose, inulin
10 or dextrose. Such sugar is especially preferred for whipping creams.

The emulsions further may contain flavour or colouring agents such as carotenoids.

15

Cooking creams may optionally contain some salt such as sodium chloride.

The emulsions may have any pH between 3 and 8. It is preferred
20 that the emulsions are neutral creams.

The emulsions may be prepared by any suitable process. For example the process includes the steps of mixing all ingredients, sterilisation, e.g by heating to about 120 to
25 150 °C, homogenisation, cooling and filling into packaging material.

Reference is also made to WO-A-01/41586 and EP-A-691080 which disclose suitable processes for preparing oil in water emulsions.

30

The invention is illustrated by the following examples.

General

General methods

5

1. Viscosity determination

Viscosity (dPa.s) is determined as shear stress / shear rate by the Haake method.

Haake viscosimeter type VT02 was used supplied with head

10

No.3, in measure beaker with diameter of 5 cm at a temperature of 5 or 10 °C. The viscosity was measured after a few seconds once the reading was constant, at a rotation speed of 62.5 rotations per minute (rpm). The measurement is to be carried out after 3 days storage at 5 °C.

15

2. Measurement of hardness/post hardening

Apparatus used: Stevens Texture Analyser model LFRA

Probe used: plastic cylinder with diameter of 1 inch

20

Settings of the Stevens Texture analyser:

Penetration depth: 4 mm

Penetration speed: 0.5 mm/sec

The hardness value is determined in grams/cm².

The temperature is 10°C.

25

Post hardening is determined after the product has been whipped to a maximum SV in about 3 to 4 minutes. The % post hardening is the absolute difference between the Stevens value of the whipped product at 10 °C immediately after whipping and 1 day after whipping on storage at 10°C divided by the Stevens value immediately after whipping.

30

3. Whipping performance

A Kenwood chefKM300tm mixer with a bowl of 4.4 l and a wire whisk is connected with a potentiometer. The mixer was
5 operated at speed 6 (maximum of mixer is 7) with 270 to 300 g of emulsion.

270 to 300 grams of emulsion were added (5 to 10 °C) to the 4.4 litre bowl of the mixer with wire whisk attachment.

The emulsion is whipped at high speed (6) until the power
10 input recorded with the potentiometer is at maximum. The time required to obtain an optimum in the resistance determined by the potentiometer is the whip time.

4. Determination of specific volume (S.V.)

15 The specific volume of the whipped emulsion was measured by filling a steel cup with known volume and weight and levelling the top. The weight of the filled cup was measured.

S.V. is the volume of the whipped emulsion in the cup
20 divided by the weight of whipped emulsion in cup (ml/g).

5. The solid fat content can be measured by a suitable analytical method such as NMR. The method used is low resolution NMR with Bruker Minispec apparatus. Reference is
25 made to the Bruker minispec application notes 4,5 and 6. Solid fat measurements were done on fat blend only.

The percentage of solid fat determined by the low resolution NMR technique is defined as the ratio of the response obtained
30 from the hydrogen nuclei in the solid phase and the response arising from all the hydrogen nuclei in the sample. The product of this ratio and one hundred is termed the low resolution NMR solids percent. No correction is made for variations in the

proton density between solid and liquid phase. The NMR solids percent for a sample measured at t °C was given the symbol N_t .

5

Suitable instruments adapted to determine the solids fat content are the Bruker Minispecs p20itm, pc20tm, pc120tm, pc120stm, NMS120tm and MQ20tm.

10 Stabilisation and tempering procedure was as indicated before:

- melt fat at 80 °C
- 5 minutes at 60 °C
- 60 minutes at 0 °C
- 30-35 minutes at each chosen measuring temperature.

15

The solid fat content measurement as used herein is described in AOCS official method Cd 16b-93 (direct method, parallel

NB: this method is different from the so called Solid fat Index
20 (SFI), which is described in AOCS official method Cd 10-57.).

Process

Ingredients and amounts are as indicated in the Examples. The
25 process for preparing was as follows.

An aqueous phase was prepared by heating water to 75 °C
Protein, sugar, gums, thickener or other ingredients were added.

The mixture was treated in an Ultra turraxtm for 5 minutes.

30 A fat phase was prepared by heating the fat blend to 75 °C
Emulsifiers were added to the heated fat blend and the
resulting mixture was stirred together with a blade stirrer for
5 minutes.

The fat phase and the aqueous phase as prepared above were mixed at 75 °C and subjected to treatment in an Ultra Turraxtm for at least 2 minutes until a homogeneous emulsion resulted.

5 In further processing the resulting mixture (pre-mix) was pre-heated to 80 °C and subjected to direct steam injection to 142 °C, while holding for 5 seconds. The resulting mixture was flash cooled to 80 °C and homogenised in one step at 200 Bar (1 step in a APV Gaulin homogeniser). The mixture was then cooled
10 to 10 °C and filled aseptically in sterile glass jars.
Storage was at 5 °C.

The general cream composition was as follows:

15

	Amount in wt%
Fat blend	20
monoglycerides	0.38
Skim milk powder and butter milk powder	5.25
Guar gum Edicol 60/70	0.075
Kappa carrageenan	0.01
Locust bean gum	0.04
Water	Up to 100

The fat blend was varied for examples 1-4

Fat blend	1 comparative	2	3	4
Rapeseed oil		10		20
CN				
Palm kernel oil	25			10
Interest blend of 60wt% palm oil and 40wt% palm kernel oil	50	70	75	
Interest blend of 60% palm oil stearine and 40% coconut oil			25	70
Fully hardened Palm kernel oil (mp 39°C)	25	20		
N10	63.1	56.5	60.5	56
N35	1.0	2.3	3.7	4
H ₂ U/HM ₂ +H ₂ M	0.22	0.33	0.5	0.35
H ₂ U/M ₃	0.35	0.99	3.69	1.5
H ₃	2.2	2.7	4.4	5.0
H ₂ M	8.8	9.7	11.5	11.7
H ₂ U	5.9	8.1	10.8	7.5
HM ₂	17.8	14.4	10.1	10.0
M ₃	16.7	8.1	2.9	5.2
Laurics (wt on total fat)	70	48	40	38
% Trans level	< 1	< 1	< 1	< 1

	1	2	3	4
Results				
Viscosity (dPas after 5°C for 8 weeks)	1.6	2	1.5	2
Cycling stability Viscosity after cycling 5/25/5°C	80 dPa.s	2 dPa.s	1.5	2
Whip time (min)	2	4	4	4
SV	2.84	3.31	3.65	3.13
Post hardening at 10°C (%)	Less than 5%	Less than 5%	Less than 5%	Less than 5%
Stevens value 10°C of whipped cream (g)	51	15	15	44

Claims

1. Oil in water emulsion comprising emulsifier, and 5 to 40 wt% fat wherein the fat is characterised by a ratio of H_2U (triglycerides of 2 saturated fatty acids with chain length of at least 16 carbon atoms and one cis-unsaturated fatty acid) in weight % on total fat divided by HM_2 (triglycerides of one saturated fatty acid with chain length of at least 16 carbon atoms and two saturated fatty acids with chain length of 10 to 14 carbon atoms) in weight % on total fat, plus H_2M (triglycerides of two saturated fatty acid with chain length of at least 16 carbon atoms and one saturated fatty acid with chain length of 10 to 14 carbon atoms) in weight % on total fat, is from 0.25 to 3.
2. Oil in water emulsion according to claim 1 wherein the fat is characterised by a ratio of H_2U (triglycerides of 2 saturated fatty acids with chain length at least 16 carbon atoms and one cis-unsaturated fatty acid) in weight % on total fat , divided by M_3 (triglycerides of three saturated fatty acids with chain length of 10 to 14 carbon atoms) in weight% on total fat, of at least 0.3.
3. Oil in water emulsion according to claim 1 wherein $H_2U/(HM_2 + H_2M)$ is from 0.3 to 3, more preferred from 0.3 to 2, most preferred from 0.5 to 0.80.
4. Oil in water emulsion according to any of claims 1-3 wherein the ratio of H_2U/M_3 is at least 0.5, more preferred at least 0.7, even more preferred at least 0.9.

5. Oil in water emulsion according to any of claims 1-4 wherein the ratio of H_2U/M_3 is from 0.5 to 10.
6. Oil in water emulsion according to any of claims 1-5 wherein the amount of laurics is from 20 to 60 wt%, preferably 30 to 60 wt%, more preferred from 40 to 60 wt% on total fat.
7. Oil in water emulsion according to any of the previous claims wherein the solid fat content of the fat at 35 °C is at most 10%, preferably at most 8%, more preferred at most 5%, even more preferred at most 4%.
8. Oil in water emulsion according to any of the previous claims wherein the solid fat content of the fat at 10 °C is at least 50%, preferably at least 55%, more preferred from 60 to 70%.
9. Oil in water emulsion according to any of the previous claims wherein the amount of H_2U is from 5 to 20 wt%, preferably from 6-12 wt% on total fat.
10. Oil in water emulsion according to any of the previous claims wherein the emulsifier comprises monoglycerides in an amount of from 0.2 to 0.5 wt% on total emulsion weight.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 03/12503

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A23D7/00 A23L1/035 A23L1/19 B01F17/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A23D A23L B01F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, FSTA, BIOSIS, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	HAAHR A M ET AL: "Flavour release of aldehydes and diacetyl in oil/water systems." FOOD CHEMISTRY 71 (3, COST ACTION 96: FOOD AND FLAVOUR) 355-362 2000 DEP. OF SEAFOOD RES., DANISH INST. FOR FISHERIES RES., TECH. UNIV. OF DENMARK, DK-2800 LYNGBY, DENMARK. TEL. +45-4525-2591. FAX +45-4588-4774. E-MAIL AMH(A)DFU.MIN.DK, XP002273824 * page 356, column 1, paragraph 3 - column 2, paragraph 2 *	1-9
X	GB 1 504 027 A (MALAYSIA RUBBER RES INST) 15 March 1978 (1978-03-15) * page 1, lines 11-15; claims 1-3 * --- -/--	1-9



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

18 March 2004

Date of mailing of the international search report

06/04/2004

Name and mailing address of the ISA^a

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Georgopoulos, N

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 03/12503

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 431 554 A (BAUR RUDOLF) 14 February 1984 (1984-02-14) * column 1, lines 44-49; claims 1, 2, 5 and 7-9 *	1-9
X	WO 94 10237 A (BARLOW IAN JOHN ; JOHNSON & SON INC S C (US)) 11 May 1994 (1994-05-11) * page 3, lines 9-26; examples 1-3 and 11-17; claims 1, 3 and 11 *	1-9
X	DATABASE WPI Section Ch, Week 197817 Derwent Publications Ltd., London, GB; Class D13, AN 1978-30724A XP002273825 -& JP 53 026803 A (ASAHI ELECTROCHEMICAL CO LTD), 13 March 1978 (1978-03-13) abstract	1-9
X	DATABASE WPI Section Ch, Week 198104 Derwent Publications Ltd., London, GB; Class B04, AN 1981-04648D XP002273826 -& JP 55 148056 A (ASAHI DENKA KOGYO KK), 18 November 1980 (1980-11-18) abstract	1-9
X	PATENT ABSTRACTS OF JAPAN vol. 005, no. 020 (C-042), 6 February 1981 (1981-02-06) -& JP 55 148055 A (ASAHI DENKA KOGYO KK), 18 November 1980 (1980-11-18) abstract	1-9
X	DATABASE WPI Section Ch, Week 198404 Derwent Publications Ltd., London, GB; Class D13, AN 1984-021088 XP002273827 -& JP 58 212752 A (ASAHI DENKA KOGYO KK), 10 December 1983 (1983-12-10) abstract	1-9
A	EP 0 824 869 A (UNILEVER PLC ; UNILEVER NV (NL)) 25 February 1998 (1998-02-25) * page 2, lines 13-26; page 4, lines 16-30; page 5, lines 6-9; examples 8 and 9, claims 1, 4 and 7 *	1-10
A	US 5 587 195 A (SASSEN CORNELIS L) 24 December 1996 (1996-12-24) * column 3, lines 1-12 and 29-35; claims 1 and 4-6 *	1-10

-/--

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 03/12503

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages .	Relevant to claim No.
A	<p>US 4 791 000 A (HOLEMANS PIETER M J ET AL) 13 December 1988 (1988-12-13) * column 7, line 67 - column 8, line 2, examples 1 and 5; claims 1-5 *</p> <p>-----</p>	1-10

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 03/12503

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
GB 1504027	A	15-03-1978	MY 40578 A	31-12-1978
US 4431554	A	14-02-1984	CH 646193 A5 DE 3035059 A1	15-11-1984 22-04-1982
WO 9410237	A	11-05-1994	AT 181090 T CA 2147886 A1 DE 69325285 D1 DE 69325285 T2 EP 0667883 A1 GR 3031058 T3 WO 9410237 A1 US 5849838 A	15-06-1999 11-05-1994 15-07-1999 30-09-1999 23-08-1995 31-12-1999 11-05-1994 15-12-1998
JP 53026803	A	13-03-1978	JP 59004107 B	27-01-1984
JP 55148056	A	18-11-1980	NONE	
JP 55148055	A	18-11-1980	JP 1436510 C JP 62042572 B	25-04-1988 09-09-1987
JP 58212752	A	10-12-1983	JP 1746277 C JP 4035139 B	25-03-1993 10-06-1992
EP 0824869	A	25-02-1998	EP 0641167 A1 EP 0824869 A1 GR 3031674 T3 AT 183363 T AT 250864 T AU 675949 B2 AU 4315493 A CA 2135515 A1 CN 1085390 A ,B DE 69326062 D1 DE 69326062 T2 DE 69333232 D1 DK 641167 T3 DK 824869 T3 WO 9324017 A1 ES 2136663 T3 JP 10095993 A JP 8503974 T JP 3137981 B2 KR 162514 B1 US 5431948 A US 5554408 A	08-03-1995 25-02-1998 29-02-2000 15-09-1999 15-10-2003 27-02-1997 30-12-1993 09-12-1993 20-04-1994 23-09-1999 02-03-2000 06-11-2003 13-03-2000 26-01-2004 09-12-1993 01-12-1999 14-04-1998 30-04-1996 26-02-2001 16-11-1998 11-07-1995 10-09-1996
US 5587195	A	24-12-1996	AT 175842 T AU 701066 B2 AU 2409395 A CA 2187025 A1 CZ 9603284 A3 DE 69507467 D1 DE 69507467 T2 DK 758845 T3 WO 9530336 A1 EP 0758845 A1 ES 2128057 T3	15-02-1999 21-01-1999 29-11-1995 16-11-1995 16-04-1997 04-03-1999 19-08-1999 13-09-1999 16-11-1995 26-02-1997 01-05-1999

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 03/12503

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5587195 A		GR 3030015 T3 HU 75988 A2 PL 317159 A1 SK 145296 A3	30-07-1999 28-05-1997 17-03-1997 04-06-1997
US 4791000 A	13-12-1988	NL 8501957 A AU 579483 B2 AU 5976686 A BE 905066 A2 CA 1289004 C DE 3661396 D1 EP 0209176 A1 JP 62014743 A ZA 8605078 A	02-02-1987 24-11-1988 15-01-1987 08-01-1987 17-09-1991 19-01-1989 21-01-1987 23-01-1987 30-03-1988